

Universal Remote Control URC Feature Comparison Chart - Not to be used as a specification.

www.AV-Outlet.com	MX-3000	TX-1000	MX-950	MX-900	MX-850	MX-650	MX-350
Prepared by AV Outlet Disputanta, VA 23842 1-877-271-5398 Fax: 1-866-454-8405							
Compatible with the MSC-400	Yes	Yes	Yes	Yes	No	No	No
PC Programmable	Yes - USB	Yes - USB	Yes - USB	Yes - USB	Yes - USB	No	No
Rechargeable Battery	Yes - Lithium Ion	No	Yes - Lithium Ion	No	No	No	No
Docking Station	Yes	No	Yes	No	No	No	No
RF Capable	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Includes RF Base Staion	No	No	No	No	No	No	No
LCD Touch Screen	Yes - Very Customizable	Yes - 12 Buttons	No	No	No	No	No
LCD Display	Customizable Color w/ built-in Templates - Image Files can be used as buttons. Max Size 320 x 240 pixels.	Yes	Import images for use as buttons. Max size 64 x 64 Pixels. Images are converted to shades of gray.	Yes	Yes	Yes	Yes
# of Hard Buttons	14	29	49	45	49	48	33
Side Display Buttons	0	0	10	6	10	10	5
Favorites Channel Button	Programmable	Programmable	Programmable	Programmable	Yes	Yes	Yes
Backlighting Motion Activated	Yes	No	Yes	No	No	No	No
Sound Signalling for Buttons	Yes - Ability to import wav files	Preprogrammed Tones Only	Yes - Ability to import wav files	Preprogrammed Tones Only	No	No	No
Clock on Display	Yes	Yes	Yes	No	No	No	No
Memory	16Mb Flash	8Mb Flash	16Mb Flash	8Mb Flash	Flash	Flash	Flash
MonoChrome LCD	No	Yes	Yes	Yes	Yes	Yes	Yes
LCD Colors	65,535 Colors	Backlight Variations of RGB	Backlight Variations of RGB	Backlight Variations of RGB	Backlight	Backlight	Backlight
IR Addressing	6 IR addressable outputs per base station - RF Base Station not Included with Remote						
RF Addressing	Address upto 15 individual RF base stations. RF Base Station not Included with Remote						
IR Range	30' - 50'	30' - 50'	30' - 50'	30' - 50'	30' - 50'	30' - 50'	30' - 50'
IR Learning Frequencies	15kHz to 100kHz	15kHz to 460kHz	15kHz to 460kHz	15kHz to 460kHz	15kHz to 460kHz	15kHz to 460kHz	15kHz to 100kHz
RF Frequency	418MHz	418MHz	418MHz	418MHz	418MHz	418MHz	418MHz
RF Range	50' - 100'	50' - 100'	50' - 100'	50' - 100'	50' - 100'	50' - 100'	50' - 100'
# of Devices Controlled	255	40	255	40	20	20	10
Menu Pages for each Device	255	40	255	40	4	4	8
Macro Capability	255 Steps Each	255 Steps Each	255 Steps Each	255 Steps Each	190 Steps Each	190 Steps Each	190 Steps Each
Macro Variables Allowed	Yes	No	Yes	No	No	No	No
LCD Size	3.5"		1.5" x 2.7"		1.4" x 2.1"	1.4" x 2.1"	0.875" x 1.875"
Weight (with Batteries)	10.4oz	31.4oz	10.4oz	14oz	8oz	8oz	8oz
Size (L x W x H)	7"x2.312"x1.18"	6.46"x5.39"x1.66"	9.625"x2.312"x1"	8"x 2.25"x1.25"	9.0"x3.0"x2.1"	9.0"x3.0"x1.3"	8.5" x 2.5" x 1"